

Synchronism Unit

ACC-SCU-4S-NG

Managed power supply and synchronism unit with 4 ports for base stations and professional radiolinks



| | |
|-----------------------|--|
| Connectors | Data, power supply y syncr.: RJ45 / Power supply: IEC 320-C14, male / GPS Antenna GPS: femaleTNC |
| LED Indicators | Power supply injection (green) / synchronism injection (yellow). Per port. Gps status indicator and GPS antenna Management : Connectivity and 10 / 100Mbps |
| Managing Network | 10/100Mbps Ethernet |
| Sensitivity | Tracking: -160dBm Acquisition: -146 dBm |
| PPS Accuracy | ±25 ms Maximum acquisition time 40 s |
| Antenna | Maximum gain 25dB Impedance 50Ω Power Supply 5V, 100mA max. |
| Management Interfaces | Command Line Interface (CLI) via SSH (remote) or serie port (local) XML-RPC for remote management Integrated web |
| Pinout | Pairs 1/2 (+), 3/6 (-) |
| Main Features | Monitoring power supplied per port |
| Power Supply | Input: 88-264VAC - 40A / Output: 48VDC |
| Consumption | ≤ 75W at full load |
| Power | 13W/port - 52W max. total aggregate |
| Temperature | From 0°C to +70°C (operating). From -40°C to +85°C (storage) |
| Dimensions | 44 x 14 x 4,5 cm |
| Weight | 2Kg |
| Standard | IEEE 802.3 at |